



Proof, Photo & Production media PRODUCT DATASHEET



EFI Proof Paper 5200XF Semiglossy



EFI 5200XF Semiglossy universal microporous coated paper is designed for offset and gravure contract proofing. The paper contains no optical brighteners which minimises metamerism and reduces measurement errors during the profiling process. (L*96 / a*0 / b*0). EFI 5200XF gives outstanding results when used in conjunction with the latest generation of printer inks (K3, Lucia, Vivid, etc.). EFI 5200XF is supplied with EFI, Fogra and PEFC back print and is very suitable for contract proofing as per ISO 12647-7 as well as GRACOL/SWOP standards.

Description:

Semiglossy coated paper
Wide color gamut
No optical brighteners
Fast drying (Instant-dry)
Universal use
PEFC 100% certified



Application:

Proofing
Photo

Technical data:

Weight	200	g / m ²
Thickness	210	μ
Opacity	95	%
Gloss [Tappi 75°]	40	%
L*a*b* Paper white	96 / 0 / 0	
Storage	15 - 30 °C (40 - 60% RH)	

Size

Sheet		Rolls	Core	Rolls	Core
DIN A4	(210 x 297 mm)	32,9 cm x 35 m	(13") 3"*	106,7 cm x 35 m	(42") 3"*
SUPER A4	(241 x 340 mm)	43,2 cm x 35 m	(17") 3"*	111,8 cm x 35 m	(44") 3"*
DIN A3	(297 x 420 mm)	43,2 cm x 50 m	(17") 3"*	127,0 cm x 35 m	(50") 3"*
DIN A3+	(330 x 483 mm)	61,0 cm x 35 m	(24") 3"*	137,0 cm x 35 m	(54") 3"*
DIN A2	(420 x 594 mm)	61,0 cm x 50 m	(24") 3"*	152,4 cm x 35 m	(60") 3"*
		91,4 cm x 35 m	(36") 3"*		

*) supplied with each two adapters 3" to 2" core



Important: Before using our print media, please verify that it is suitable for use with your printer. We shall not assume liability for non-performance of the print media resulting from changes beyond our control in printing inks or printers. Specifications are subject to change without notice. This product data sheet is intended to be used as a guideline only. Storing conditions: Please keep product in the supplied boxes for best possible protection. Product must be stored in a cool and dry environment, exposure to sun light is to be avoided.